POLYCOM°

A POLYCOM DATA SHEET

Polycom[®] SoundPoint[®] IP 335 High Definition IP Phone

A powerful dual-line solution combining advanced telephony with the unmatched clarity of Polycom HD Voice[™]

The Polycom[®] SoundPoint[®] IP 335 phone is designed to bring a high-quality, cost effective solution to cubicle workers/call center operators through advanced telephony features and HD Voice technology, making voice communication more clear and productive. Utilizing its high resolution backlit display, RJ-9 headset port, and Polycom HD Voice technology, the SoundPoint IP 335 phone delivers a business grade telephony endpoint at an entry-level price.

Unsurpassed Voice Quality and Clarity

With a best-in-class design for high-fidelity voice reproduction, the SoundPoint IP 335 also incorporates wideband audio for over twice the voice clarity of standard phones. Patented Polycom Acoustic Clarity[™] technology provides crystal-clear, noise- and echo-free audio, while hold, pick-up, transfer, and three-way local conferencing features make managing calls simple and intuitive. Capabilities such as shared call/bridged line appearance, built-in xHTML microbrowser, and a RJ-9 headset port extend functionality for more advanced requirements.

Polycom Powers Smarter Conversations

The SoundPoint IP 335 is a key element in a broader Polycom portfolio of best in class solutions and services for voice, video, telepresence, and collaboration infrastructure. As a global leader in open standard Unified Communications (UC) solutions, Polycom's award-winning IP telephony and conferencing solutions make it easy for people to interact and maximize productivity over any network, in just about any environment, anywhere around the globe. That's why more organizations worldwide choose Polycom to enable UC everywhere.

Learn More

To find out how Polycom solutions can help your organization, visit us at www.polycom.com or speak with a Polycom Account Representative.



Benefits

More efficient and productive conversations

Unparalleled clarity through Polycom HD Voice and patented Polycom Acoustic Clarity

Broad interoperability

Certified to interoperate with a broad array of SIP call control platforms to enable flexibility and choice for customers

Easy provisioning and management Supports a wide range of industry standard methods to facilitate simple, large-scale deployment and

Intuitive interface

management of devices

High resolution graphical 102 x 33 pixel grayscale LCD with adjustable backlighting



Lines (Direct Numbers)

- Up to 2 lines with up to 8 simultaneous calls total Display
- 102 x 33 pixel backlit grayscale graphical LCD
- LED backlight with custom intensity control
- Message Waiting Indicator (MWI) LED

Feature Kevs

- 3 context-sensitive "soft" keys
- 2 line keys with bi-color (red/green) LED .
- 2 feature keys ("Menu" and "Dial")
- 4-way navigation key cluster with center "Select" key
- 2 volume control keys
- . Dedicated hold key
- . Dedicated headset key
- Dedicated hands-free speakerphone key
- Dedicated microphone mute key
- Optional Messages Key

Headset and Hearing Aid Compatibility

- Dedicated RJ-9 headset port
- Compliant with ADA Section 508
- Recommendations: Subpart B 1194.23 (all) Hearing Aid Compatible (HAC) handset for magnetic coupling to TIA 504-A and ITU P370
- standards Compatible with commercially available TTY
- adapter equipment

Audio Features

- Polycom HD Voice technology delivers life-like voice quality for each audio path - the handset, the hands-free speakerphone and the optional headset1
- Full-duplex hands-free speakerphone
- Type 1 compliant with IEEE 1329 full duplex standards Codecs: G.722 (wideband), G.711 µ/A, G.729A
- (Annex B) and iLBC Individual volume settings with visual feedback for each audio path
- Voice activity detection
- Comfort noise fill
- DTMF tone generation/DTMF event RTP payload .
- . Low-delay audio packet transmission
- Adaptive jitter buffers
- Packet loss concealment
- Acoustic echo cancellations
- . Background noise suppression

Call Handling Features²

- Shared call/bridged line appearance
- Busy Lamp Field (BLF)
- Flexible line appearance (one or more line keys can be assigned for each line extension)
- Distinctive incoming call treatment/call waiting Call timer
- Call transfer, hold, divert (forward), pickup
- Called, calling, connected party information
- Local three-way conferencing
- One-touch speed dial
- Call waiting

www.polycom.com

. Remote missed call notification

Polycom Worldwide Headquarters

4750 Willow Road, Pleasanton, CA 94588 1.800.POLYCOM or +1.925.924.6000

for any purpose other than the recipient's personal use, without the express written permission of Polycom

- Intercom
- Automatic off-hook call placement
- Do not disturb function

Other Features

- Interoperability with Microsoft[®] LCS 2005 for telephony and presence³
 - Compatibility with Microsoft Office Communicator and Windows® Messenger 5.1 Clients
- Enabled for Polycom Productivity Suite
- Local feature-rich GUI
- Time and date display
- User-configurable contact directory and call history (missed, placed and received)
- Wave file support for call progress tones
- Unicode UTF-8 character support. Multilingual user interface encompassing Danish, Dutch, English (Canada/US/UK), French, German, Italian, Norwegian, Polish, Russian, Slovenian, Spanish, Swedish

Protocol Support

IETF SIP (RFC 3261 and companion RFCs)

Network and Provisioning

- Two 10/100 Mbps Ethernet ports
- Manual or dynamic host configuration protocol (DHCP) network setup
- Time and date synchronization using SNTP
- FTP/TFTP/HTTP/HTTPS server-based central provisioning for mass deployments
- Provisioning and call server redundancy supported
- Web portal for individual unit configuration
- QoS Support IEEE 802.1p/Q tagging (VLAN), Layer 3
- TOS and DSCP
- Network Address Translation (NAT) support for static configuration and "Keep-Alive" SIP signaling
- RTCP support (RFC 1889)
- Event logging
- Syslog
- Local digit map
- Hardware diagnostics Status and statistics reporting

Security

- Transport Layer Security (TLS)
- Secure Real-time Transport Protocol (SRTP)
- Encrypted configuration files
- Shipped with X.509 certificate installed
- **Digest authentication**
- Password login
- Support for URL syntax with password for boot server
- HTTPS secure provisioning
- Support for signed software executables

Power

- Built-in, auto-sensing IEEE 802.3af Power Over Ethernet (Class2)
- External universal input AC adapter (optional⁴; 24V DC@500mA)

© 2011 Polycom, Inc. All rights reserved. POLYCOM[®], the Polycom "Triangles" logo and the names and marks associated with Polycom's products are trademarks and/or service marks of Polycom, Inc. and are registered and/or common law marks in the United States and various other countries. All other trademarks are property of their respective owners. No portion hereof may be reproduced or transmitted in any form or by any means,

Approvals

- FCC Part 15 (CFR 47) Class B
- . ICES-003 Class B
- . EN55022 Class B
- CISPR22 Class B
- AS/NZS CISPR22 Class B
- VCCI Class B
- EN55024
- CE

. **RoHS** Compliant GOST-R

A-Tick

C-Tick

ANATEL

TRA

Safetv

NZ Telepermit

IEC60950-1

EN60950-1

UL60950-1

AS/NZS 60950-1

Operating Conditions

Storage Temperature

Base stand

CAN/CSA C22.2 No.60950-1-03

-40 to +70°C (-40 to +160°F)

SoundPoint IP 335 console

Handset with handset cord

Network (LAN) cable

6.7 in x 5.7 in x 6.9 in

Product registration card

(17 cm x 17 cm x 17.5 cm)

Part Numbers /UPC Codes

Phone weight: 1.9 lb (0.861 kg)⁵

Unit Box Dimensions / Weight

(25 cm x 10.5 cm x 29.5 cm)

2.9 lbs (1.3 kg)⁵

Country of Origin

call/applications server.

Singapore, Malaysia

the world

0.65 lb (0.294 kg)

Master Carton Quantity

10 in x 4.2 in x 11.6 in (W x H x D)

1. To enjoy all the benefits of Polycom HD Voice when using the

3. Features supported on SoundPoint IP 335 require SIP 3.2.2 or

Optional AC Adapter 5-Packs, Part Numbers/UPC Codes
2200-17877-001/610807690269 for NA, CALA, Taiwan

2200-17877-012/610807630283 for Australia/New Zealand
2200-17877-015/610807690290 for UK, Ireland, HK,

· 2200-17877-122/610807690306 for India, Europe, Rest of

2200-17877-002/610807690276 for Japan

2200-17877-016/610807693437 for Korea
2200-17877-022/610807693444 for China

more complete listing/description of features.

2200-17877-119/610807715719 for Switzerland

5. Measurements taken for PoE. Power supply weights estimated at

6. Refer to the Administrator's Guide for Polycom UC Software for a

😽 POLYCOM°

2264 0111

phone in the headset mode, you must use a wideband headset. 2. Some of these features need to be supported by an appropriate

2200-12375-025/610807694670 for all markets

Quick Start Guide

SoundPoint IP 335 Comes With:

Temperature: 0 to 40°C (+32 to 104°F)

Relative Humidity: 5% to 95%, non-condensing

. KCC

.

.

.

Size

Weight

Ten

Thailand

Warrantv

later

1 Year