

CISCO 100BASE-FX SFP FAST ETHERNET INTERFACE CONVERTER ON GIGABIT SFP PORTS

The Cisco® 100BASE-FX Small Form-Factor Pluggable (SFP) Fast Ethernet Interface Converter (GLC-GE-100FX=) is a hot-swappable device that plugs into a Gigabit Ethernet SFP port on Cisco Catalyst® 3750 Series, 3560 Series, and 2970 Series switches. The Cisco SFP provides full-duplex 100-Mbps connectivity between switches over multimode fiber (MMF) infrastructures. It offers investment protection and an easy migration path for customers moving to Gigabit Ethernet connections in the future.

The 100BASE-FX SFP operates on ordinary multimode fiber optical link spans of up to 2 kilometers (km) in length. Customers implementing Cisco 100BASE-FX SFP can use 1000BASE-X SFPs in the future (including SX, LX/LH, ZX, and coarse wavelength-division multiplexing SFPs).



TECHNICAL SPECIFICATIONS

Platform Support

The Cisco 100BASE-FX SFP on Gigabit SFP ports is supported on Cisco Catalyst 3750, 3560, and 2970 series switches.

Connectors and Cabling

- Connectors: Dual LC connector

Table 1 shows cabling specifications for the 100BASE-FX SFP installed on a Gigabit Ethernet SFP port. The minimum cable distance is 6.5 feet (2 meters [m]).

Table 1. SFP Port Cabling Specifications

| SFP | Wavelength (nm) | | | Fiber Type | Core Size (micron) | Modal Bandwidth (MHz/km) | Cable Length |
|---------------|-----------------|------|------|------------|--------------------|--------------------------|----------------|
| | Min | Typ | Max | | | | |
| GLC-GE-100FX= | 1270 | 1300 | 1380 | MMF | 62.5 | 500 | 2 km (6562 ft) |
| | | | | | 62.5 | | |
| | | | | | 50.0 | | |
| | | | | | 50.0 | | |

Standards

The Cisco 100BASE-FX SFP is compatible with standards as specified in IEEE 802.3z.

Table 2. Fiber Loss Budgets for 100BASE-FX-SFP on Gigabit Ethernet SFP Ports

| SFP | Type | Cabling | Transmit (dBm) | | Receive (dBm) | |
|---------------|------------|-----------------|----------------|-----|---------------|-------|
| | | | Min | Max | Min | Typ |
| GLC-GE-100FX= | 100BASE-FX | 50/125-micron | -23.5 | -14 | -33.5 | -11.8 |
| | | 62.5/125-micron | -20 | -14 | -33.5 | -11.8 |

Dimensions

- Maximum dimensions (HxWxD): 0.39 x 2.23 x 0.54 in. (9.80 x 56.70 x 13.8 mm)

Environmental Conditions and Power Requirements

- Operating temperature range: 0 to 45 degrees C
- Storage temperature range: -40 to 80 degrees C
- Predicted mean time between failure (MTBF): 12,820,512 hours
- Power consumption: 1.5 W

Table 3. Electrical Power Interface

| Parameter | Symbol | Minimum | Typical | Maximum | Units |
|----------------|--------|---------|---------|---------|-------|
| Supply Current | Is | - | 405 | 450 | mA |
| Surge Current | Isurge | - | 350 | - | mA |
| Input Voltage | Vcc | 3.315 | 3.3 | 3.465 | V |

Warranty

- Standard warranty: 90 days
- Extended warranty (optional): Available under a Cisco SMARTnet® support contract

Ordering Information

| SFP | Product Number |
|--|----------------|
| Cisco 100BASE-FX SFP for Gigabit SFP ports | GLC-GE-100FX= |

Regulatory and Standards Compliance

- IEC 60825-1



Corporate Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 526-4100

European Headquarters

Cisco Systems International BV
Haarlerbergpark
Haarlerbergweg 13-19
1101 CH Amsterdam
The Netherlands
www-europe.cisco.com
Tel: 31 0 20 357 1000
Fax: 31 0 20 357 1100

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
www.cisco.com
Tel: 408 526-7660
Fax: 408 527-0883

Asia Pacific Headquarters

Cisco Systems, Inc.
168 Robinson Road
#28-01 Capital Tower
Singapore 068912
www.cisco.com
Tel: +65 6317 7777
Fax: +65 6317 7799

Cisco Systems has more than 200 offices in the following countries and regions. Addresses, phone numbers, and fax numbers are listed on **the Cisco Web site at www.cisco.com/go/offices.**

Argentina • Australia • Austria • Belgium • Brazil • Bulgaria • Canada • Chile • China PRC • Colombia • Costa Rica • Croatia • Cyprus • Czech Republic • Denmark • Dubai, UAE • Finland • France • Germany • Greece • Hong Kong SAR • Hungary • India • Indonesia • Ireland Israel • Italy • Japan • Korea • Luxembourg • Malaysia • Mexico • The Netherlands • New Zealand • Norway • Peru • Philippines • Poland Portugal • Puerto Rico • Romania • Russia • Saudi Arabia • Scotland • Singapore • Slovakia • Slovenia • South Africa • Spain • Sweden Switzerland • Taiwan • Thailand • Turkey • Ukraine • United Kingdom • United States • Venezuela • Vietnam • Zimbabwe

Copyright © 2004 Cisco Systems, Inc. All rights reserved. CCIP, CCSP, the Cisco *Powered* Network mark, Cisco Unity, Follow Me Browsing, FormShare, and StackWise are trademarks of Cisco Systems, Inc.; Changing the Way We Work, Live, Play, and Learn, and iQuick Study are service marks of Cisco Systems, Inc.; and Aironet, ASIST, BPX, Catalyst, CCDA, CCDP, CCIE, CCNA, CCNP, Cisco, the Cisco Certified Internetwork Expert logo, Cisco IOS, the Cisco IOS logo, Cisco Press, Cisco Systems, Cisco Systems Capital, the Cisco Systems logo, Empowering the Internet Generation, Enterprise/Solver, EtherChannel, EtherSwitch, Fast Step, GigaStack, Internet Quotient, IOS, IP/TV, iQ Expertise, the iQ logo, iQ Net Readiness Scorecard, LightStream, Linksys, MGX, MICA, the Networkers logo, Networking Academy, Network Registrar, *Packet*, PIX, Post-Routing, Pre-Routing, RateMUX, Registrar, ScriptShare, SlideCast, SMARTnet, StrataView Plus, Stratum, SwitchProbe, TeleRouter, The Fastest Way to Increase Your Internet Quotient, TransPath, and VCO are registered trademarks of Cisco Systems, Inc. and/or its affiliates in the United States and certain other countries.

All other trademarks mentioned in this document or Web site are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (0402R) 204108.15_ETMG_KW_10.04

