
















Cable Guide



Cable Part Numbers	Length	Sideband Support	To Controller	To Drives/Backplane	Compatible Controllers			
CBL-RA8087SATAB-10M*	1.0m	✓	SFF-8087 	Discrete 	Internal connectivity 9750 (-4i, -8i, -4i4e, -16i4e, -24i4e) 9280 (-4i4e, -16i4e, -24i4e) 9240 (-4i, -8i), 9260 (-4i, -8i, -16i) 9261-8i, 9201-16i 9211 (-4, -8i), 9212-4i4e 9690SA (-4i, -8i, -4i4e)			
CBL-SFF8087-SATAB-06M	0.6m	✓		Discrete 				
CBL-SFF8087-SATAB-10M	1.0m	✓						
CBL-SFF8087OCF-05M	0.5m							
CBL-SFF8087OCF-06M	0.6m			SFF-8087 				
CBL-SFF8087OCF-10M	1.0m							
CBL-RA8087SB-10M	1.0m	✓						
CBL-SFF8087SB-08M	0.8m	✓		SFF-8087 				
CBL-SFF8087SB-05M	0.5m	✓						
CBL-SFF8087SB-06M	0.6m	✓						
CBL-SFF8087-05M	0.5m							
CBL-SFF8087-06M	0.6m							
CBL-RA8087-08M*	0.8m							
CBL-RA8087-10M*	1.0m							
CBL-SFF8087-10M	1.0m							
CBL-SFF8088SAS-10M	1.0m					SFF-8088 	SFF-8088 	External connectivity 9750 (-8e, -4i4e, -16i4e, -24i4e) 9280 (-8e, -4i4e, -16i4e, -24i4e) 9200 (-8e, -16e), 9201-16e 9212-4i4e, 9207-8e SAS6160 SAS Switch 
CBL-SFF8088SAS-20M	2.0m							
CBL-SFF8088ASAS-100M (Active)	10m							
CBL-SFF8088ASAS-200M (Active)	20m							
CBL-SAS8087OCF-06M	0.6m		SFF-8087 	SFF-8482 	Internal connectivity 9750 (-4i, -8i, -4i4e, -24i4e) 9240 (-4i, -8i), 9260 (-4i, -8i, -16i) 9261-8i, 9280 (-4i4e, -24i4e) 9201-16i, 9211 (-4i, -8i), 9212-4i4e 			

* Connector to controller is right angled.

Cable Part Numbers	Length	Sideband Support	To Controller	To Drives/Backplane	Compatible Controllers
CBL-SFF8644-8088-10M	1.0m		SFF-8644 	SFF-8088 	External connectivity 9380 (-8e, -4i4e) 9206-16e 9300 (-8e, -4i4e) 
CBL-SFF8644-8088-20M	2.0m				
CBL-SFF8644-8088-60M	6.0m				
CBL-SFF8644-10M	1.0m		SFF-8644 	SFF-8644 	
CBL-SFF8644-20M	2.0m				
CBL-SFF8644-60M	6.0m				
CBL-SFF8643-8087-06M	0.6m		SFF-8643 	SFF-8087 	Internal connectivity 9300 (-4i, -8i, -4i4e) 9361 (-4i, -8i) 9341 (-4i, -8i) 9380-4i4e 
CBL-SFF8643-8087-08M	0.8m				
CBL-SFF8643-8087-10M	1.0m				
CBL-SFF8643-06M	0.6m		SFF-8643 	SFF-8643 	
CBL-SFF8643-08M	0.8m				
CBL-SFF8643-10M	1.0m				
CBL-RA8643-04M*	0.4m				
CBL-SFF8643-SATA5B-05M	0.5m	✓	SFF-8643 	x4 SATA 	
CBL-SFF8643-SATA5B-06M	0.6m	✓			
CBL-SFF8643-SATA5B-10M	1.0m	✓			
CBL-SFF8643-SAS8482SB-06M	0.6m	✓	SFF-8643 	SFF8482 	

* Connector to controller is right angled.

Avago Technologies products serve four primary target markets: wireless communications, wired infrastructure, enterprise storage, and industrial. Avago Storage by LSI™ offers the industry's broadest portfolio of storage solutions, backed by decades of experience and trusted by the world's leading server and storage suppliers. Avago provides the building blocks for storage solutions that help customers understand, prioritize, store and protect critical data.

The Avago 12Gb/s SAS portfolio includes MegaRAID® controller cards, host bus adapters (HBAs), advanced software options, Syncro® shared DAS solutions and SAS storage ICs, including RAID-on-Chip (ROCs), I/O controllers and expanders.



Visit the Avago Storage by LSI website at: lsi.com

Avago, Avago Technologies, MegaRAID, and the Storage by LSI logo are trademarks of Avago Technologies. All other trademarks are the property of their respective owners.

Copyright ©2014 Avago Technologies. All rights reserved. > 25.11.14 SG0108.EU