



*Products that use these mics*  
C40, C60, C90 and their Profiles  
MXP - 3000, 6000, Edge

TPM20 - C40



TPM20



*Products that use these mics*  
C40 Profile  
MX200, MX300, EX90, C20, SX20

## AT871UG

### Cisco PID:

CTS-MIC-DIR=

### Cisco Description:

Directional Microphone, includes 7.5M cable

### Notes

This microphone is an Audio Technica AT871UG, modified especially by AT for Cisco  
The pickup pattern is cardioid in a hemisphere above the table  
Connector is mini-XLR at the microphone, and standard male XLR at the other end of the cable  
"UG" indicates that the mic is rated for rejecting cell phone and RF noise  
Ships with Edge MXP, 6000 MXP

### Reference

Check specifications for 871R on [audiotechnica.com](http://audiotechnica.com) - will be similar if not identical

## AT841UG

**Cisco PID:**

CTS-MIC-OMNIDIR=

**Cisco Description:**

Onni Directional Microphone, includes 7.5M cable

**Notes**

This microphone is an Audio Technica AT841UG, modified especially by AT for Cisco  
The pickup pattern is omnidirectional in a hemisphere above the table  
Connector is mini-XLR at the microphone, and standard male XLR at the other end of the cable  
"UG" indicates that the mic is rated for rejecting cell phone and RF noise  
Ships with C40 / C60 / C90 Integrator Pack, and with C60 / C90 Profiles

**Reference**

Check specifications for U841A on audiotechnica.com - will be similar if not identical

## TPM20

**Cisco PID:**

CTS-QSC20-MIC=

**Cisco Description:**

Performance Microphone 20

**Notes**

This microphone is Cisco-developed and manufactured  
It is omnidirectional and has a mute button and LED. The LED is red when muted, green when not muted  
It has a 4-conductor mini jack at the end of the attached 7.5M cable  
It ships with C20, SX20, MX200 and MX300  
It can be used with the EX90 - defeats the internal mic when used

**Reference**

SPECIFICATIONS\_CTS-QSC20-MIC.pdf *(includes pinouts)*

## TPM20 for C40 Profile

**Cisco PID:**

TBD

**Description:**

Performance Microphone 20 for C40 Profile

**Notes**

This microphone is Cisco-developed and manufactured  
It is omnidirectional - there is no mute button or LED  
It has a 4-conductor mini jack at the end of the attached 7.5M cable  
It is used for the C40 Profile

**Reference**

SPECIFICATIONS\_CTS-QSC20-MIC.pdf *Will be similar in coverage and sensitivity*

All contents are Copyright © 1992–2012 Cisco Systems, Inc. All rights reserved. This document is Cisco Confidential.